


PE 100 RC FM-Line Tees, injected



Product details:

- black
- injected, with elongated spigot, for butt welding and electrofusion welding
- FM Approval 1613 15 bar / 218 psi
- DIN EN ISO 15494/B, DIN EN 12201/3, DIN EN 1555/3

Product image for illustration purposes only.

SDR	d (mm)	e (mm)	le1 (mm)	z1 (mm)	PN (bar)	Length (mm)	kg/piece	Art. No.
11	90	8,2	80	137	16	274	0,940	010024918
11	110	10,0	88	161	16	322	1,579	010024919
11	125	11,4	98	175	16	350	2,220	010024920
11	140	12,7	104	200	16	400	3,180	010024921
11	160	14,6	104	206	16	413	4,290	010024922
11	180	16,4	143	260	16	520	6,900	010024923
11	200	18,2	124	250	16	500	8,330	010024924
11	225	20,5	128	277	16	554	11,700	010024925
11	250	22,7	132	291	16	582	13,950	010024926
11	280	25,4	139	312	16	624	18,860	010024927
11	315	28,6	153	345	16	690	26,460	010024928
11	355	32,2	167	410	16	820	38,100	010024929
11	400	36,3	198	457	16	914	52,010	010024930
11	450	40,9	198	477	16	954	74,585	010024931
11	500	45,4	218	525	16	1050	100,000	010024932

All information provided in respect of technical data shall be considered non-binding. This information does not constitute a guarantee of specific properties or qualities and shall not be construed as a warranty in regard to product condition, durability or service life. Subject to modifications and errors. Our standard terms and conditions apply. For further information, please contact our applications engineering team: pipingsystems@simona.de.